

Disk Handwheels

Plastic, Bushing / Spindle Stainless Steel













- Bore code
- **B** Without keyway
- With keyway DIN 6885-1 P9



- A Without handle
- R With revolving handle

J	3

d ₁	d₂ H7 Bore		b	d ₃	d ₄	d ₅	d ₆	d ₇	h	I ₁	l ₂	l ₃	r	Ø Handle
	Type A	Type R												
100	10	10	24	22	20	30	25	27	9	22	34	60	39	15,5
125	-	12	28	26	24	35	28	31	11	27	39,5	60	49	18
150	14	14	32	26	24	38	30	34	10	30	44	65	58	22
200	20	20	39	40	38	50	40	44	13	36	53	90	81	25

Specification

Wheel body

Plastic, Polypropylene (PP)

- Reinforced, shock-resistant
- Operating temperature 0 °C to +80 °C
- · Black, matte finish

Hub bushing

Stainless steel AISI 30

Threaded bushing

Brass

Cover

Plastic, light gray

Revolving handle

Plastic, Polyamide (PA)

- · Black, matte finish
- Spindle

Stainless steel AISI 304

RoHS

Disk handwheels GN 521.5 have recessed grips at their back.

The cover conceals clamping elements, e.g. countersunk washers, as well as protruding and recessed shafts. For mounting, the cover is pushed in by hand. For dismantling, the cover can be raised and taken off by applying moderate pressure in the rim of the cover.

see also	Page
GN 521 Disk Handwheels (Polypropylene, Hub Bushing Steel)	QVX
GN 520.2 Disk Handwheels (Phenolic Resin, Hub Bushing Stainless Steel)	QVX

Technical Information

QVX
QVX
QVX
QVX
QVX

GN 184.5 Countersunk Washers (for Axial Fixing)

QVX

How to order		d ₁		
		Bore code		
1 2 3 4 GN 521.5-125-B12-R	3	d ₂		
	4	Туре		

